



Item	Part name	Qty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au plating over Ni
2	Plunger	1	Leaded Brass	Au plating over Ni
3	Spring	1	Stainless steel wire	
4				
5				

Table 1 Mechanical performance	
working height	1.90mm
Durability	70±20gf <3.1> 10000cycle

- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M.
  - 2 Mechanical performance(See the table 1)
  - 3 Electrical performance
  - 4 Resistance: 50mOhm Max.Current rating: 1.0A
  - 5 Packaging Spec.Comformance to EIA 481
  - 6 RoHS complaint.

Rev.	Revision record.	Date.
	NEW	2011/05/23
	Revision record.	

Top-Link Electronics Ltd.		Type Customer drawing		Unit mm		Weight	
TOLERANCES UNLESS OTHER SPECIFIED		DWN: Qin		APVD:		101118-1	
0.0	±0.15	CHK:		REL:		PART NUMBER	
0.00	±0.10	Name		POGO PIN PG-1.1-0.4-1.03-1.78-2.40		1	
0.000	±0.05	Scale		Size A4		Page 1/1	
Angle: ±1°		1:1		DWG No. C-101118		Rev. A	
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX.IDO NOT SCALE PRINT.		Name		DWG No.		Page 1/1	
		POGO PIN		C-101118		Rev. A	

三佐株式会社

DIST  
---  
DIST  
---