



- Notes:
- △Material:
 - 1)Plunger & Body : CuZn36 Pb3, H02 (C36000) or CuZn39 PB3 or CuZn38 PB2 or CuZn36(C2700).
 - 2)Spring : Stainless steel wire
 - 2 Plating
 - 1)Body: 0.1um Gold plating over min. 1.4um Nickel plating
 - 2)Plunger: 0.4um Gold plating over min. 1.4um Nickel plating
 - 3 Mechanical
 - 1)Total stroke : 1.4mm
 - 2)Durability: 10,000 cycle min.
 - 4 Electrical
 - 1)Contact resistance: 30mOhm Max.
 - 2)Operating voltage: 36VDC

USED DN
-

LDC	-
DIST	-

LTR	REVISION	APVD	DATE
	new		08/03/28

DIMENSIONS IN MM	
TOLERANCES UNLESS OTHER SPECIFIED	
0	= ±
0.0	= ±0.15
0.00	= ±0.10
0.000	= ±
ANGLE: ±1°	
SURF. TEXTURE: 32/	
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX DD NOT SCALE PRINT	

MATL	HT TR	FIN
DWN	APVD	
Jim	Lansing	
CHK	REL	
Andy		
NAME		
PGGD PIN		
PG-2.0-0.5-1.5-3.5-5.0		
SCALE	DWG ND.	
1:1	A4	C-101029

三佐株式会社

101029-1
PART NUMBER

4 3 2 1